

NEW PORTABLE A/C UNIT

AMERICOOOL



# WPC-4000

## INCLUDED PARTS

- 5"X20" COOL AIR DUCT ASSEMBLY
- ALUMINUM EVAPORATOR FILTER
- ALUMINUM CONDENSER FILTER
- CONDENSATE TANK
- 12" EXHAUST FLANGE

## KEY FEATURES

- 16,800 Btu/h
- 115V, 20 Amps
- OPERATING RANGE OF 64-104 DEGREES
- EXTREMELY PORTABLE AND WORKS GREAT WITH GENERATORS
- SPOT COOL AND ROOM COOL MODES AVAILABLE
- COLD AIR NOZZLES CAN BE REPLACED WITH INCLUDED GRILL

## OPTIONAL ACCESSORIES



WPCPLENUM-4000  
12" Ambient  
Air Adapter



WPCDUCT-0540  
5"X40" Cool Air  
Duct Assembly



WPCCONN-0503  
Cool Air  
Air Adapter



WPCSENSOR  
16 FT Temperature  
Sensor Line



WPCREMOTE  
Remote Control  
Unit (26 ft Line)



WPCPUMP-115  
115 Condensate  
Pump Kit

800.680.0725 | [INFO@AMERICOOOLING.COM](mailto:INFO@AMERICOOOLING.COM)

2892 BELLFLOWER BLVD., #443

LONG BEACH, CA 90815

OFFICE: 800.680.0725 | FAX: 562.394.0539

[WWW.AMERICOOOLING.COM](http://WWW.AMERICOOOLING.COM)

P/N: AMC-INSRT001

# WPC-4000 SPECIFICATIONS



Intertek

All AmeriCool units are ETL listed for use in the U.S. and

SPECIFICATIONS	UNIT	WPC-4000
Cooling Capacity	Btu/h	16,800
Power Supply	Phase	Single
	Volts	115
	Hertz	60
Size (W x D x H)	Inches	20.5 x 26 x 40.9
Weight	Lbs	181
Current Consumption	Amps	15.5
Circuit Breaker Size	Amps	20
Power Consumption	kW	1.7
Compressor Input	kW	1.3
Air Flow (High/Low) Evaporator	CFM	470 / 400
Air Flow Condenser	CFM	1,250 / 1,120
Fans - Motor Output - High/Low	kW	363 / 261
Air Filter		Aluminum / Vinyl Chloride
Nema Plug	Type	5-20P
Power Cord Gauge	Awg	12AWG
Power Cord Length	ft	6
Refrigerant	Type	R410A
	oz	35.2
Operating Conditions	°F	64~104
Hot Air Duct Diameter	Inches	12
Maximum Exhaust Duct Length	ft	50
Condensate Tank	Gal	3.17
Available From		May, 2012



Specifications are subject to change without notice.