AMERICOOL

PO BOX 243 AUBURN MA 01501 P: 888-726-6158 INFO@AMERICOOLLLC.COM

PORTABLE DEHUMIDIFIER

ADH-130

1111

THE ULTIMATE PORTABILITY AND SIMPLICITY

AmeriCool portable climate solution units are designed for even the harshest environments, though they are ideal for a multitude of different situations. These versatile systems are ideal for a host of applications to provide a solution for virtually any situation.

PRODUCT SPECIFICATIONS

PE

DI

REFORMANCE DATA	
Voltage & Frequency	AC 115V 60 Hz
Power Consumption & Current	945W/8.3A @ 80°F, 60% RH 1140W/10.6A @ 86°F, 80% RI
Refrigerant Charge	R410A/ 26.8 oz (760)
Dehumidify Capacity	130 ppd @ 80°F , 60% RH 200 ppd @ 86°F, 80% RH
Maximum Design Pressure	High Side: 522 psig (3.6MPa) Low Side: 240 psig (1.65MPa)
BCSC	15A
Compressor Input	RLA: 9.1A LRA:50.5A
Fan Motor Power	0.187HP
MENSIONS	
	22 E 20 20 in

Width×Length×Height 33.5×20×20 in. Weight 107 lbs.

